



The Pura Vida Ultra Violet Water Sterilizer effectively eliminates microorganisms in your pool or spa, keeping your water cleaner and healthier, while dramatically reducing chemical usage.



Sterilizes pool water using UV light technology, creating a healthier, more natural swimming environment



Destroys bacteria, viruses & algae without affecting pH levels



Eco-Friendly! Using less chemicals, leaves less toxins in our environment



Saves money on chemicals and helps to extend the life of your pool equipment



Access our installation manual here!



Clean Water. Pure Life. puravidauv.ca



## Built in lamp monitor - audible and visual indication of lamp life

- 316L stainless steel chamber for maximum reflective disinfection.
- Drain port for easy winterization with zinc anode
- User friendly bayonet style lamp connector (no extra tools needed)
- Proprietary low pressure (LP) coated UV lamps with ceramic bases for durability and long life (10,000 hours)
- Auto sensing dual voltage controller for plug in or hard wired use
- For vertical or horizontal installation


# **Equipment Specifications**


Model	PV2-42C	PV2-82C
Flow Rate	42 GPM	82 GPM
	159 lpm	310.4 lpm
	9.5 m³/hr	18.6 m³/hr
Port Size	1.5" MNPT	2" MNPT
Electrical	90-265V/50-60Hz. (IEC power cord included)	
Plug Type	American, Nema 5/15, 3 wire for all 110V systems	
Lamp Watts	67	101
Replacement Lamp	PV2RL-600HO	PV2RL-950HO
Replacement Sleeve	PV2RQ-600	PV2RQ-950
Replacement Controller	PV2RCHO-4.12	
Chamber Material	316L Stainless Steel, A249 Pressure Rated Tubing, Polished & Passivated	
Chamber Dimensions	3.5 x 26.9" (8.9 x 68.3 cm)	3.5 x 40.7" (8.9 x 103.4 cm)
Controller Dimensions	8.6 x 4.2 x 4" (21.7 x 10.8 x 10.2 cm)	
Operating Pressure	0.7-10.3 bar (10-150 psi)	
Operating Water Temperature	2-40° C (36-104° F)	
Lamp Change Reminder	YES (4-digit LED display)	
Visual Lamp Out Indicator	YES	
Audible Lamp Out Indicator	YES	
Shipping Weight	7.9 kg (17.5 lbs)	10.0 kg (22.1 lbs)

#### \*A recommended minimum level of chlorine or bromine must be maintained at all times.

### **Dimensions**

C





	PV2-42C	PV2-82C
Α	27.5" (700mm)	41.3" (1050mm)
В	20.1" (510mm)	32.8" (834mm)
С	8.4" (214mm)	8.8" (223mm)
D	3.5" (89mm)	3.5" (89mm)

## Manufacturer's Warranty

CHAMBERS - Three (3) year Limited Warranty
ELECTRONICS - Three (3) year Limited Warranty
UV LAMPS - One (1) year Limited Warranty
QUARTZ SLEEVES - One (1) year Limited Warranty



